

FORMULASHELL(TM) SAE 10W-30 MOTOR OIL (SJ)
50203
04/29/97

SHELL MATERIAL SAFETY DATA SHEET
BE SAFE. READ OUR PRODUCT SAFETY INFORMATION ... AND PASS IT ON.
PRODUCT LIABILITY LAW REQUIRES IT!

***** MATERIAL SAFETY DATA SHEET 71165 - 01

FORMULASHELL(TM) SAE 10W-30 MOTOR OIL (SJ) SH MSDS: 71165 - 01
04/29/97

MANUFACTURER'S NAME AND ADDRESS
SHELL OIL COMPANY
PRODUCT SAFETY & COMPLIANCE
P.O. BOX 4320
HOUSTON, TX 77210

TELEPHONE NUMBERS:
24 HOUR EMERGENCY ASSISTANCE
SHELL: 713-473-9461 CHEMTREC: 800-424-9300

GENERAL MSDS ASSISTANCE
SHELL: 713-241-4819

SECTION I		NAME	

PRODUCT:		FORMULASHELL(TM) SAE 10W-30 MOTOR OIL (SJ)	
CHEM NAME:		MIXTURE (SEE SECTION II-A)	ACUTE HEALTH HAZARD:
			1
CHEM FAMILY:		PETROLEUM HYDROCARBON; MOTOR OIL	FIRE HAZARD:
			1
SHELL CODE:		50203	REACTIVITY:
			0

SECTION II-A		PRODUCT/INGREDIENT
--------------	--	--------------------

NO.	COMPOSITION	CAS	PERCENT
P	FORMULASHELL SAE 10W-30 MOTOR OIL (SJ)	MIXTURE	100
1	HIGHLY REFINED PETROLEUM OILS	MIXTURE*	83-85
2	ADDITIVES	MIXTURE	15-17

* MAY CONTAIN: 64742-54-7

NFPA HAZARD RATING: HEALTH 0 FIRE 1 REACTIVITY 0

SECTION II-B | ACUTE TOXICITY DATA

NO.	ACUTE ORAL LD50 LC50	ACUTE DERMAL LD50	ACUTE INHALATION
P	NOT AVAILABLE	NOT AVAILABLE	NOT AVAILABLE
1	>5.0 G/KG (RAT)*	>5.0 G/KG (RABBIT)*	NOT AVAILABLE

* BASED ON API STUDIES.

SECTION III | HEALTH INFORMATION

THE HEALTH EFFECTS NOTED BELOW ARE CONSISTENT WITH REQUIREMENTS UNDER THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

EYE CONTACT:
LUBRICATING OILS ARE GENERALLY CONSIDERED NO MORE THAN MINIMALLY IRRITATING TO THE EYES.

SKIN CONTACT:

LUBRICATING OILS ARE GENERALLY CONSIDERED NO MORE THAN MILDLY IRRITATING TO THE SKIN. PROLONGED AND REPEATED CONTACT MAY RESULT IN VARIOUS SKIN DISORDERS SUCH AS DERMATITIS, FOLLICULITIS OR OIL ACNE.

INHALATION:

INHALATION OF VAPOR (GENERATED AT HIGH TEMPERATURES ONLY) OR OIL MIST FROM THIS PRODUCT MAY RESULT IN MILD IRRITATION OF THE UPPER RESPIRATORY TRACT.

INGESTION:

LUBRICATING OILS ARE GENERALLY CONSIDERED NO MORE THAN SLIGHTLY TOXIC IF SWALLOWED.

SIGNS AND SYMPTOMS:

IRRITATION AS NOTED ABOVE.

AGGRAVATED MEDICAL CONDITIONS:

PREEXISTING SKIN AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS:

THIS PRODUCT AND ITS COMPONENTS ARE NOT CLASSIFIED AS CARCINOGENS BY INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC), NATIONAL TOXICOLOGY

PROGRAM (NTP) OR OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA).

THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER HAS DETERMINED THERE IS

SUFFICIENT EVIDENCE FOR THE CARCINOGENICITY IN EXPERIMENTAL ANIMALS OF USED

MOTOR OILS. HANDLING PROCEDURES AND SAFETY PRECAUTIONS IN THE MSDS SHOULD

BE FOLLOWED TO MINIMIZE EMPLOYEE'S EXPOSURE TO THE USED PRODUCT.

SECTION IV | OCCUPATIONAL EXPOSURE LIMITS

NO.	OSHA		ACGIH		OTHER
	PEL/TWA	PEL/CEILING	TLV/TWA	TLV/STEL	
P	5 MG/M3*	NONE	5 MG/M3*	10 MG/M3*	

*OIL MIST, MINERAL

SECTION V | EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT: REMOVE CONTAMINATED CLOTHING/SHOES AND WIPE EXCESS FROM SKIN. FLUSH SKIN WITH WATER. FOLLOW BY WASHING WITH SOAP AND WATER.

IF IRRITATION OCCURS, GET MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL CLEANED.

INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GET MEDICAL ATTENTION.

INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION.*

NOTE TO PHYSICIAN: *IF MORE THAN 2.0 ML PER KG HAS BEEN INGESTED AND VOMITING HAS NOT OCCURRED, EMESIS SHOULD BE INDUCED WITH SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX,

GASTRIC

CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS,
LAVAGE USING A CUFFED ENDOTRACHEAL TUBE SHOULD BE
CONSIDERED.

SECTION VI | SUPPLEMENTAL HEALTH INFORMATION

NONE IDENTIFIED.

SECTION VII | PHYSICAL DATA

BOILING POINT (DEG F): HG): NOT AVAILABLE	SPECIFIC GRAVITY (H2O=1): NOT AVAILABLE	VAPOR PRESSURE (MM <0.1
---	--	----------------------------

MELTING POINT (DEG F): (AIR=1): -25 (POUR POINT)	SOLUBILITY (IN WATER): NEGLIGIBLE	VAPOR DENSITY NOT AVAILABLE
--	--------------------------------------	--------------------------------

VISCOSITY: 10-12
(CST @ 104 DEG. C)

EVAPORATION RATE (NORMAL BUTYL ACETATE = 1): NOT AVAILABLE

APPEARANCE AND ODOR: DARK RED LIQUID. SLIGHT HYDROCARBON ODOR.

SECTION VIII | FIRE AND EXPLOSION HAZARDS

FLASH POINT AND METHOD: 400 DEG F (COC)
FLAMMABLE LIMITS/% VOLUME IN AIR:
LOWER: N/AV UPPER: N/AV

EXTINGUISHING MEDIA:
USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:
MATERIAL WILL NOT BURN UNLESS PREHEATED. DO NOT ENTER CONFINED FIRE-SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE-PRESSURE NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

SECTION IX | REACTIVITY

STABILITY: STABLE HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:
AVOID HEAT, OPEN FLAMES AND OXIDIZING MATERIALS.

HAZARDOUS DECOMPOSITION PRODUCTS:
THERMAL DECOMPOSITION PRODUCTS ARE HIGHLY DEPENDENT ON THE COMBUSTION CONDITIONS. A COMPLEX MIXTURE OF AIRBORNE SOLID, LIQUID, PARTICULATES AND GASES WILL EVOLVE WHEN THIS MATERIAL UNDERGOES PYROLYSIS OR COMBUSTION.

CARBON MONOXIDE, HYDROGEN SULFIDE AND OTHER UNIDENTIFIED ORGANIC
COMPOUNDS
MAY BE FORMED UPON COMBUSTION.

SECTION X | EMPLOYEE PROTECTION

RESPIRATORY PROTECTION:
IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SECTION IV)
USE
A NIOSH-APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORD WITH 29
CFR
1910.134 USE EITHER AN ATMOSPHERE-SUPPLYING RESPIRATOR OR AN AIR-
PURIFYING
RESPIRATOR FOR ORGANIC VAPORS AND PARTICULATES.

PROTECTIVE CLOTHING:
WEAR CHEMICAL RESISTANT GLOVES AND OTHER PROTECTIVE CLOTHING AS REQUIRED
TO
MINIMIZE SKIN CONTACT. WEAR SAFETY GOGGLES TO AVOID EYE CONTACT. TEST
DATA
FROM PUBLISHED LITERATURE AND/OR GLOVE AND CLOTHING MANUFACTURERS
INDICATE
THE BEST PROTECTION IS PROVIDED BY NITRILE GLOVES.

ADDITIONAL PROTECTIVE MEASURES:

SECTION XI | ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES:
MAY BURN ALTHOUGH NO READILY IGNITABLE. USE CAUTIOUS JUDGMENT WHEN
CLEANING
UP LARGE SPILLS. *** LARGE SPILLS *** WEAR RESPIRATOR AND PROTECTIVE

CLOTHING AS APPROPRIATE. SHUT OFF SOURCE OF LEAK IF SAFE TO DO SO. DIKE AND

CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE SALVAGE VESSELS. SOAK

UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND, OR OTHER SUITABLE MATERIALS;

DISPOSE OF PROPERLY. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. ***

SMALL SPILLS *** TAKE UP WITH AN ABSORBENT MATERIAL AND DISPOSE OF PROPERLY.

SECTION XII | SPECIAL PRECAUTIONS

MINIMIZE SKIN CONTACT. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE. PROPERLY DISPOSE OF CONTAMINATED LEATHER ARTICLES, INCLUDING SHOES, THAT CANNOT BE DECONTAMINATED.

STORE IN A COOL, DRY PLACE WITH ADEQUATE VENTILATION. KEEP AWAY FROM OPEN FLAMES AND HIGH TEMPERATURES.

SECTION XIII | TRANSPORTATION REQUIREMENTS

DEPARTMENT OF TRANSPORTATION CLASSIFICATION:
NOT HAZARDOUS BY D.O.T. REGULATIONS

D.O.T. PROPER SHIPPING NAME:

OTHER REQUIREMENTS:

SECTION XIV | OTHER REGULATORY CONTROLS

THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA/TSCA INVENTORY OF
CHEMICAL
SUBSTANCES.

PROTECTION OF STRATOSPHERIC OZONE (PURSUANT TO SECTION 611 OF THE CLEAN AIR
ACT
AMENDMENTS OF 1990): PER 40 CFR PART 82, THIS PRODUCT DOES NOT CONTAIN NOR
WAS
IT DIRECTLY MANUFACTURED WITH ANY CLASS I OR CLASS II OZONE DEPLETING
SUBSTANCES.

IN ACCORDANCE WITH SARA TITLE III, SECTION 313, THE ATTACHED ENVIRONMENTAL
DATA
SHEET (EDS) SHOULD ALWAYS BE COPIED AND SENT WITH THE MSDS.

SECTION XV | STATE REGULATORY INFORMATION

BASED ON INFORMATION AVAILABLE TO SHELL, THIS PRODUCT DOES NOT CONTAIN ANY
CHEMICAL SUBSTANCE REGULATED BY A SPECIFIC STATE LIST.

SECTION XVI | SPECIAL NOTES

MSDS REVISED IN SECTION II-A TO REVISE COMPOSITION, SECTION III HEALTH
INFORMATION, SECTION XV TO REVISE STATES AND EDS SECTIONS I AND II. THE
OSHA
HAZARD EVALUATION AND REGULATORY STATUS OF THE PRODUCT HAVE NOT CHANGED.

THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE TO US AND IS BELIEVED TO BE CORRECT. HOWEVER, SHELL MAKES NO WARRANTY, EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. SHELL ASSUMES NO RESPONSIBILITY FOR INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN.

WE ARE PROVIDING OUR MOST RECENT MATERIAL SAFETY DATA SHEET AND/OR ENVIRONMENTAL DATA SHEET. IF YOU WISH TO RECEIVE UPDATES TO THIS INFORMATION, PLEASE CALL SHELL'S GENERAL MSDS ASSISTANCE LINE (713-241-4819) TO ENSURE THAT YOU ARE ADDED TO SHELL'S REGULAR MSDS DISTRIBUTION SYSTEM.

BE SAFE. READ OUR PRODUCT SAFETY INFORMATION...AND COMPLIANCE PASS IT ON. (PRODUCT LIABILITY LAW REQUIRES IT)

SHELL OIL COMPANY
PRODUCT SAFETY AND
P. O. BOX 4320
HOUSTON, TX. 77210

***** ENVIRONMENTAL DATA SHEET 71165 - 01 *****

EDS: 71165 - 01

04/29/97

PRODUCT NAME: FORMULASHELL(TM) SAE 10W-30 MOTOR OIL (SJ)
PRODUCT CODE: 50203

MANUFACTURER'S NAME AND ADDRESS
SHELL OIL COMPANY
P.O. BOX 4320
HOUSTON, TX 77210

TELEPHONE NUMBERS:
24 HOUR EMERGENCY ASSISTANCE

SHELL: 713-473-9461

CHEMTREC: 800-424-9300

FOR ADDITIONAL INFORMATION ON THIS ENVIRONMENTAL DATA PLEASE
CALL 713-241-2252

SECTION I | PRODUCT COMPOSITION

NO. COMPOSITION CAS PERCENT
=====

=====
P FORMULASHELL SAE 10W-30 MOTOR OIL (MIXTURE 100
SJ)
1 HIGHLY REFINED PETROLEUM OILS MIXTURE* 83-85
2 ADDITIVES MIXTURE 15-17

* MAY CONTAIN: 64742-54-7

SECTION II | SARA TITLE III INFORMATION

NO. EHS RQ* EHS TPQ* SEC-313 313 CATEGORY 311/312
CATEGORY
(*1) (*2) (*3) (*4) (*5)
=====

=====
BASED ON THE DATA AVAILABLE TO SHELL, THIS PRODUCT IS NOT REGULATED BY
SARA,
TITLE III.

*1 = REPORTABLE QUANTITY OF EXTREMELY HAZARDOUS SUBSTANCE, SEC 302
*2 = THRESHOLD PLANNING QUANTITY, EXTREMELY HAZARDOUS SUBSTANCE, SEC 302
*3 = TOXIC CHEMICAL, SEC 313
*4 = CATEGORY AS REQUIRED BY SEC 313 (40 CFR 372.42), MUST BE USED ON TOXIC

RELEASE INVENTORY FORM

*5 = HAZARD CATEGORY FOR SARA SEC. 311/312 REPORTING

HEALTH: H-1 = IMMEDIATE (ACUTE) HEALTH HAZARD

H-2 = DELAYED (CHRONIC) HEALTH HAZARD

PHYSICAL: P-3 = FIRE HAZARD

P-4 = SUDDEN RELEASE OF PRESSURE HAZARD

P-5 = REACTIVE HAZARD

SECTION III | ENVIRONMENTAL RELEASE INFORMATION

THIS PRODUCT IS COVERED BY EPA'S COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION AND LIABILITY ACT (CERCLA) PETROLEUM EXCLUSION. THEREFORE, RELEASES TO AIR, LAND, OR WATER ARE NOT REPORTABLE UNDER CERCLA ("SUPERFUND"). HOWEVER, UNDER SECTION 311 OF EPA'S CLEAN WATER ACT (CWA),

THIS PRODUCT IS CONSIDERED AN OIL. AS SUCH, SPILLS INTO OR LEADING TO SURFACE WATERS THAT CAUSE A SHEEN MUST BE REPORTED TO THE NATIONAL RESPONSE

CENTER, 800-424-8802.

THIS PRODUCT IS AN OIL UNDER 49 CFR (DOT) PART 130. IF SHIPPED BY RAIL OR

HIGHWAY IN A TANK WITH A CAPACITY OF 3,500 GALLONS OR MORE, IT IS SUBJECT TO

THE REQUIREMENTS OF PART 130. MIXTURES OR SOLUTIONS IN WHICH THIS PRODUCT IS

PRESENT AT 10% OR MORE MAY ALSO BE SUBJECT TO THIS RULE.

SECTION IV | RCRA INFORMATION

IF THIS PRODUCT BECOMES A WASTE, IT WOULD NOT BE A HAZARDOUS WASTE BY RCRA

CRITERIA (40 CFR 261). PLACE IN AN APPROPRIATE DISPOSAL FACILITY IN COMPLIANCE WITH LOCAL REGULATIONS.

WE ARE PROVIDING OUR MOST RECENT MATERIAL SAFETY DATA SHEET AND/OR

ENVIRONMENTAL DATA SHEET. IF YOU WISH TO RECEIVE UPDATES TO THIS INFORMATION, PLEASE CALL SHELL'S GENERAL MSDS ASSISTANCE LINE (713-241-4819) TO ENSURE THAT YOU ARE ADDED TO SHELL'S REGULAR MSDS DISTRIBUTION SYSTEM.

COMPANY SHELL OIL
77210 P.O. BOX 4320
HOUSTON, TX

FOR ADDITIONAL INFORMATION ON THIS ENVIRONMENTAL DATA PLEASE CALL
(713) 241-2252

FOR EMERGENCY ASSISTANCE PLEASE CALL
SHELL: (713) 473-9461
CHEMTREC: (800) 424-9300

THIS MSDS HAS BEEN PROVIDED IN AN ELECTRONIC FORMAT FOR USE IN THE CHEMTREC EMERGENCY RESPONSE PROGRAM AND/OR OTHER APPROVED PROGRAMS. THIS FORMAT MAY CONTAIN BLANKS WHERE INFORMATION WAS NOT AVAILABLE OR NOT APPLICABLE AND THEREFORE MAY NOT BE FULLY COMPLIANT WITH THE OSHA HAZARD COMMUNICATION STANDARD. IF YOU PURCHASE OR USE THIS SHELL PRODUCT AND HAVE NOT RECEIVED A MSDS FROM SHELL PLEASE CONTACT US AND WE WILL PROVIDE ONE. THIS WILL ENSURE THAT YOU RECEIVE UPDATES OF THIS INFORMATION.

