

ITW Permatex  
10 Columbus Blvd.  
Hartford, CT 06106 USA  
Telephone: 1-87-Permatex  
(877) 376-2839  
Emergency: 800-255-3924 (ChemTel)  
International Emergency: 00+ 1+ 813-248-0585

## Material Safety Data Sheet

### 1. PRODUCT IDENTIFICATION

**Product Name:** 765-1831 NAPA CERAMIC EXTREME BRAKE PARTS LUBRICANT 8 OZ (PTX24125)  
**Item No:** 21235  
**Product Type:** Lubricant

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component:	Weight%	ACGIH; TLV-TWA	OSHA PEL
SYNTHETIC BASE OILS (TRADE SECRET)	>90	Not listed	Not listed

### 3. HAZARDS IDENTIFICATION

**Toxicity:** May cause eye and skin irritation.  
**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation  
**Signs and Symptoms of Exposure:** Overexposure may cause eye and skin redness.  
**Aggravated Medical Condition:** Preexisting skin disorders.

### 4. FIRST AID MEASURES

**Ingestion:** If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Get medical attention/advice if you feel unwell.  
**Skin Contact:** Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

### 5. FIRE FIGHTING MEASURES

**Flash Point °F(C°):** >500°F COC  
**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.  
**Special Fire-Fighting Procedures:** Treat as oil fire. Firefighters should wear self-contained breathing apparatus.  
**Hazardous Products of Combustion:** Oxides of carbon  
**Unusual Fire/Explosion Hazards:** None.  
**Lower Explosive Limit:** n/d  
**Upper Explosive Limit:** n/d

### 6. ACCIDENTAL RELEASE MEASURES

**Spill Procedures:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

### 7. HANDLING AND STORAGE

**Storage:** Store away from heat.  
**Handling:** Avoid contact with skin and eyes. Wash thoroughly after handling. Product may cause surfaces to become slippery.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Ventilation:** Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

**Respiratory Protection:** An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Purple semi-solid

**Odor:** Mild

**Boiling Point:** n/d

**pH:** Does not apply

**Solubility in Water:** Insoluble

**Specific Gravity:** 0.94

**VOC(Wt.%):** 0

**Vapor Pressure:** Not Determined

**Vapor Density (Air=1):** > 1 (air = 1)

**Evaporation Rate:** <1 (butyl acetate = 1)

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable at normal conditions

**Hazardous Polymerization:** Will not occur

**Incompatibilities:** Strong oxidizers

**Conditions to Avoid:** Excessive heat

**Hazardous Products of Combustion:** Oxides of carbon

## 11. TOXICOLOGICAL INFORMATION

See Section 3

## 12. ECOLOGICAL INFORMATION

No data available

## 13. DISPOSAL CONSIDERATIONS

**Recommended Method of Disposal:** Disposal should be made in accordance with federal, state and local regulations.

**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

## 14. TRANSPORTATION INFORMATION

### DOT (49CFR 172)

#### U.S. Department of Transportation - DOT - 49 CFR (Ground)

**DOT Shipping Name:** Not regulated

**Hazard Class:** None

**UN/ID Number:** None

### IATA (Air)

**Proper Shipping Name:** Not regulated

**Class or Division:** None

**UN/ID Number:** None

### IMDG (Vessel)

**Proper Shipping Name:** Not regulated

**Hazard Class:** None

**UN Number:** None

**Marine Pollutant:** None

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

**California Proposition 65:** No California Prop 65 chemicals are known to be present.

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

**Product Name:** 765-1831 NAPA CERAMIC EXTREME BRAKE  
PARTS LUBRICANT 8 OZ (PTX24125)

**Item No.** 21235

## 16. OTHER INFORMATION

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety  
**Company:** ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106  
**Telephone No.:** 1-87-Permatex (877) 376-2839

**Revision Date:** May 06, 2014

**Revision Number:** 2