

# MATERIAL SAFETY DATA SHEET

SLICK 50® FUEL SYSTEM FORMULA

## 1. PRODUCT AND COMPANY IDENTIFICATION

MSDS Number: 25027

Version Date: 1/5/2007

**Product Name:** SLICK 50® FUEL SYSTEM FORMULA

**Product Use:** Fuel system cleaner

**Synonyms:** 40206016

### Company Information

SOPUS Products  
P.O. Box 4427  
Houston, TX 77210-4427  
USA

### Phone Numbers

**Medical Emergency:** 1-800-546-6040  
**Transportation Emergency (USA):** 1-800-424-9300  
**Transportation Emergency (International):**  
1-703-527-3887(Call Collect)  
**MSDS Assistance:** 1-800-546-6227  
**Fax On Demand:** 1-800-546-6227  
**Technical Assistance:** 1-800-458-4998  
**Customer Service:** 1-800-468-8397  
**Fax Number:** 713-217-3181  
**Internet Address:** www.MSDS.PZLQS.com

## 2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent Range	Hazardous in Blend
HYDROTREATED LIGHT DISTILLATE	64742-47-8	55 - 65	Yes
STODDARD SOLVENT	8052-41-3	15 - 25	Yes
PROPRIETARY ADDITIVE	MIXTURE	15 - 20	No

This product meets the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### Hazards:

**Flammable/Combustible** X **Acute Toxin** X **Chronic Toxin** -- **Carcinogen** --  
**Pressure** -- **Reactive** -- **Exposure Limit** X **Target Organ** -- **Other** --

**Other:** This product contains petroleum naphthas and/or solvents which are a complex blend of light petroleum distillates.

## 3. HAZARDS IDENTIFICATION

### Emergency and Hazards Overview

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

**NFPA Ratings:** **Health** 2 **Flammability** 2 **Reactivity** 0

**Primary Route of Exposure:** **Skin** X **Inhalation** -- **Eye** --

### Health Effect Information

**Eye Contact:** Avoid eye contact. This product may be slightly irritating to the eyes upon direct contact. Based on testing of similar products and/or components. Exposure to high concentrations of vapors may be irritating to the eyes.

**Skin Contact:** Avoid skin contact. This product may cause slight skin irritation upon direct contact. Based on testing of similar products and/or components. Prolonged or repeated skin contact may result in dryness, chapping, and reddening. May be absorbed through skin.

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50@ FUEL SYSTEM FORMULA

Page 2 of 8

**Inhalation:** This product is not expected to pose an inhalation hazard under conditions of foreseeable use. Avoid prolonged inhalation of vapors. This product may be considered a low health hazard unless inhaled in very high concentrations. Acute and chronic exposure to vapors may be irritating to the respiratory tract. Severe intoxication may lead to drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Intentional misuse by deliberately concentrating and inhaling this product can be harmful or fatal.

**Ingestion:** Do not ingest. Ingestion is expected to be relatively non-toxic unless aspiration occurs. Aspiration may lead to chemical pneumonitis which is characterized by pulmonary edema and hemorrhage and may be fatal. Signs of lung involvement include increased respiratory rate, increased heart rate, and a bluish discoloration of the skin. Coughing, choking, and gagging are often noted at the time of aspiration. Gastrointestinal discomfort may develop, followed by vomiting with a further risk of aspiration. Severe oral intoxication will lead to intense burning of the throat and may result in drowsiness, dullness, numbness, and headache followed by dizziness, weakness, and nausea. Loss of consciousness and convulsions followed by death may result.

**Medical Conditions Aggravated by Exposure:** Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

**Other:** No information available

---

## 4. FIRST AID INFORMATION

**Eye Contact:** Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If irritation persists, seek medical attention.

**Skin Contact:** No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. Use a hand or skin lotion to prevent dryness.

**Inhalation:** If victim exhibits signs of vapor intoxication remove to fresh air. If discomfort persists seek medical attention.

**Ingestion:** Do not induce vomiting due to aspiration hazard. If vomiting occurs lower head below knees to avoid aspiration. Seek immediate medical attention.

**Notes to Physician:** No information available

**Other:** No information available

---

## 5. FIRE AND EXPLOSION INFORMATION

### Flammable Properties

**Flash Point:** 111 F, 43.9 C

**Test Method:** ASTM D-93 (P.M.C.C.)

### Flammable Limits in Air

**Upper Percent:** No data available

**Lower Percent:** No data available

**Autoignition Temperature:** No data available

**Test Method:** No information available

**NFPA Classification:** Class II combustible liquid

**Extinguishing Media:** Use water spray (fog), dry chemical, foam, or carbon dioxide.

### Fire Fighting Measures

**Special Fire Fighting Procedures and Equipment:** No special fire fighting procedures are required.

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50® FUEL SYSTEM FORMULA

Page 3 of 8

**Unusual Fire and Explosion Conditions:** Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

**Hazardous Combustion By-Products:** None

**Other:** No information available

---

## 6. ACCIDENTAL RELEASE MEASURES

**Personnel Safeguards:** Remove all sources of ignition. Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Provide adequate ventilation during clean-up.

**Regulatory Notifications:** No notification required

**Containment and Clean up:** Do not allow spill to enter sewers or watercourses. Absorb with solvent absorbent material.

**Other:** No information available

---

## 7. HANDLING AND STORAGE INFORMATION

**Handling:** All ignition sources in the area should be controlled. Do not open or use in unventilated, enclosed or confined spaces.

**Storage:** Do not transfer to unmarked containers. Store in a cool, well ventilated area in closed containers away from heat, sparks, open flame or oxidizing materials.

### Empty Container Warnings

**Drums:** Not applicable

**Plastic:** Empty container may retain product residues. Do not reuse this container.

**Other:** No information available

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

### Exposure Limits and Guidelines

Component	CAS No.	Exposure Limit
STODDARD SOLVENT	8052-41-3	OSHA - PEL: TWA 500 ppm ACGIH - TLV: TWA 100 ppm

### Personal Protective Equipment

**Eye/Face Protection:** Eye protection is not required under conditions of normal use. If material is handled such that it could be splashed into eyes, wear plastic face shield or splash-proof safety goggles.

**Skin Protection:** No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. Launder soiled clothes.

**Respiratory Protection:** Respiratory protection is not required under conditions of normal use. If excessive levels of mists or vapors are generated while using this product, use an organic vapor respirator. All respirators must be NIOSH certified. See Section 3, Health Effect Information, Inhalation.

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50® FUEL SYSTEM FORMULA

Page 4 of 8

**Personal Hygiene:** Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

## Engineering Controls / Work Practices

**Ventilation:** General room ventilation is normally sufficient to prevent buildup of hazardous concentrations. If product is used in enclosed or confined spaces, adequate ventilation must be provided to prevent buildup of vapors or mists.

**Other:** The OSHA PEL and ACGIH TLV for stoddard solvent is 525 mg/m<sup>3</sup>. NIOSH recommended limits for petroleum distillates are 350 mg/m<sup>3</sup> (10-hr TWA) and 1800 mg/m<sup>3</sup> (15-min ceiling).

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b> Clear amber	
<b>Odor:</b> Solvent	<b>Vapor Pressure:</b> 1.52
<b>Physical state:</b> Liquid	<b>Vapor Density (air=1):</b> No data available
<b>pH:</b> Not applicable	<b>Percent Volatile by Volume:</b> No data available
<b>Boiling Point:</b> 185 F, 85 C	<b>Volatile Organic Content:</b> No data available
<b>Melting Point:</b> Not applicable	<b>Molecular Weight:</b> No data available
<b>Specific Gravity:</b> 0.83	<b>Average Carbon Number:</b> No data available
<b>Pour Point:</b> No data available	<b>Viscosity @ 100 F:</b> No data available
	<b>Viscosity @ 40 C:</b> No data available
<b>Solubility in Water:</b> Negligible in water	
<b>Octanol / Water Coefficient: Log K<sub>ow</sub> =</b> No data available	

---

## 10. STABILITY AND REACTIVITY INFORMATION

**Chemical Stability:** Stable

**Conditions to Avoid:** Keep away from heat, sparks, open flames and other ignition sources.

**Incompatible Materials to Avoid:** May react with strong oxidizing agents.

**Other:** No information available

---

## 11. TOXICOLOGICAL INFORMATION

**Primary Eye Irritation:** No information available

**Primary Skin Irritation:** No information available

**Acute Dermal Toxicity:** No information available

**Subacute Dermal Toxicity:** No information available

**Dermal Sensitization:** No information available

**Inhalation Toxicity:** No information available

**Inhalation Sensitization:** No information available

**Oral Toxicity:** No information available

**Mutagenicity:** No information available

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50@ FUEL SYSTEM FORMULA

Page 5 of 8

**Carcinogenicity:** Light hydrocarbons such as stoddard solvent, VM & P naphtha and C10-C11 isoparaffins have produced kidney damage in male rats, but not in female rats or mice. The Environmental Protection Agency (EPA) has concluded that rat kidney damage and tumors induced by light petroleum hydrocarbons are not relevant to humans. Various naphthas tested were not carcinogenic in mouse skin painting studies conducted by the American Petroleum Institute (API). The International Agency for Research on Cancer (IARC) has concluded that petroleum solvents are Group 3 substances, "not classifiable as to their carcinogenicity to humans".

**Reproductive and Developmental Toxicity:** No information available

**Teratogenicity:** No information available

**Immunotoxicity:** No information available

**Neurotoxicity:** No information available

**Other:** No information available

---

## 12. ECOLOGICAL INFORMATION

**Aquatic Toxicity:** May be toxic to aquatic organisms.

**Terrestrial Toxicity:** No information available

**Chemical Fate and Transport:** This substance is expected to biodegrade at a moderate rate and be "inherently" biodegradable according to OECD guidelines.

**Other:** No information available

---

## 13. DISPOSAL INFORMATION

**Regulatory Information:** Dispose of residual products and empty containers responsibly. Refer to state and local regulations for additional disposal requirements.

**Waste Disposal Methods:** Waste material may be landfilled or incinerated at an approved facility. The discarded material should be recycled if possible.

**Other:** No information available

---

## 14. TRANSPORTATION INFORMATION

**U.S. Department of Transportation (DOT)**

**Highway / Rail (Bulk):** NOT APPLICABLE

**Highway / Rail (Non-Bulk):** Consumer Commodity, ORM-D

**For US shipments, US DOT law requires the shipper to determine the proper shipping description of the material that is being shipped. The shipping information and description contained in this section may not be suitable for all shipments of this material, but may help the shipper determine the proper shipping description for a particular shipment.**

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50@ FUEL SYSTEM FORMULA

Page 6 of 8

## International Information

Vessel: IMDG Regulated:   X   IMDG Not Regulated:   --    
Air: ICAO Regulated:   X   ICAO Not Regulated:   --  

Other: No information available

---

## 15. Regulatory Information

**Regulatory Lists Searched:** The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.

**Health & Safety:** 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325

**Environmental:** 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depleters, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCOMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs

**International:** 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification

**State Lists:** 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances

**Inventories:** 80 - Canada - Domestic substances , 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA , 85 - China Inventory

### **Regulatory Search Results:**

HYDROTREATED LIGHT DISTILLATE: 80, 81, 83, 84, 85

STODDARD SOLVENT: 15, 16, 17, 23, 50, 61, 63, 65, 66, 67, 69, 80, 81, 83, 84, 85

**U.S. TSCA Inventory:** All components of this material are on the US TSCA Inventory.

**SARA Section 313:** Consumer products are not regulated under SARA, Title III, Section 313.

**IARC:** No information available

### **SARA 311 / 312 Categories**

Acute:   X   Chronic:   --   Fire:   X   Pressure:   --   Reactive:   --  

Not Regulated:   --  

### **Canadian WHMIS Classification**

Class B - Flammable and Combustible Material, Division 3, Combustible Liquid  
Class D - Poisonous and infectious material, Division 2B, Toxic Material

### **European Union Classification**

#### **Hazard Symbols:**

Harmful / Xn / X in square.

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50® FUEL SYSTEM FORMULA

Page 7 of 8

Dangerous for the environment / N / dead tree and fish in square

## Risk Phrases:

R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

## Safety Phrases:

S2: Keep out of the reach of Children.

S23: Do not breathe gas/fumes/vapour/spray.

S24: Avoid contact with skin.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

**Other:** No information available

---

## 16. OTHER INFORMATION

### Health and Environmental Label Language

Front Label:

DANGER: HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.

Read carefully other cautions on back.

Back Label:

DANGER: Contains petroleum distillates. Prolonged and repeated skin contact may cause drying of skin.

PRECAUTIONARY MEASURES: Keep away from heat, sparks, flames and other ignition sources. Avoid breathing of mists and vapors. Use only in well ventilated areas. Keep container closed. Avoid skin and eye contact. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. Call physician immediately. If inhaled, breathe fresh air. For skin or eye contact, wash thoroughly with water.

KEEP OUT OF REACH OF CHILDREN.

### MSDS Revisions

**Previous Version Date:** 9/6/2002

### Previous Version Information

No information available

### Other

No information available

### Prepared By:

SOPUS Products

P.O. Box 4427

Houston, TX 77210-4453 USA

# MATERIAL SAFETY DATA SHEET

MSDS Number: 25027

SLICK 50® FUEL SYSTEM FORMULA

Page 8 of 8

**Disclaimer of Warranty:** The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, SOPUS Products must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information, the results to be obtained from the use thereof, or that any such use do not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.