



STA-LUBE HYDRAULIC & JACK OIL

MSDS Number

BCTGR

National Stock Number

9150-00N009781

Product Name

STA-LUBE HYDRAULIC & JACK OIL

Manufacturer

STA LUBE INC

Product Identification

Product ID: STA-LUBE HYDRAULIC & JACK OIL

MSDS Date: 06/01/1987

FSC: 9150

NIIN: 00N009781

MSDS Number: BCTGR

Responsible Party

STA-LUBE, INC.

3039 ANA STREET

RANCHO DOMINGUEZ, CA 90221

Emergency Phone: 303 893-7774(POISINDEX)

Info Phone: 213 537-5650

Preparer: NELSON ALLEY

Cage: FO996

Contractor

STA-LUBE, INC.

RANCHO DOMINGUEZ, CA 90221

US

(213) 537-5650

Cage: FO996

Ingredients

SOLVENT REFINED NAPHTHENIC AND PARAFFINIC PETROLEUM OILS

CAS: 64741-89-5

RTECS: PY8041500

Fraction By Weight: 98%

OSHA PEL5MGM3

ACGIH TLV: 5MGM3

PROPRIETARY ZN,P,S ADDITIVE

Fraction By Weight: 1%

OSHA PEL OSHA PEL

ACGIH TLV: ACGIH TLV

Hazards

LD50 LC50 Mixture:



Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:AVOID PRODUCTION OF OIL MISTS.
Explanation of Carcinogenicity:N/A FPN
Effects of Overexposure:DERMATITIS IN SENSITIVE PEOPLE. DIZZINESS FROM OIL FOGS.
Medical Cond Aggravated by Exposure:DERMATITIS.

First Aid

First Aid:INHALE:OIL FOGS REMOVE TO FRESH AIR-CALL PHYSICIAN.
SKIN:DERMATITIS-WASH WITH SOAP AND WATER.USE GLOVES. INGEST:CALL MD IMMEDIATELY

Fire Fighting

Flash Point Method:COC
Flash Point:380F/191.4C
Extinguishing Media:FOAM/WATER FOG, DRY CHEMICAL, CO*2, VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS
Fire Fighting Procedures:STANDARD PETROLEUM PROCEDURES: USE NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT
Unusual Fire/Explosion Hazard:

Accidental Release

Spill Release Procedures:REMOVE WITH ABSORBENT MATERIAL SUCH AS SAND, CLAY, ETC.REMOVE FROM WATER BY SKIMMING. KEEP OUT OF SEWERS. WASH WITH SAFETY SOLVENT AND/OR DETERGENT AND WATER.
Neutralizing Agent:

Handling

Handling and Storage Precautions:PETROLEUM OILS ARE RELATIVELY NON-VOLATILE PRODUCTS&PRESENT NO VAPOR HAZARDS AT ROOM TEMPERATURE.AVOID PRODUCTION OF OIL MISTS.
Other Precautions:KEEP CLEAN AND DRY.

Exposure Controls

Respiratory Protection:NONE NORMALLY NEEDED. NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN
Ventilation:CONSULT LOCAL SAFETY/HEALTH AUTHORITIES IF ADDITIONAL GUIDANCE IS NECESSARY
Protective Gloves:FOR SENSITIVE PERSONS.
Eye Protection:AS NECESSARY-NOT NORMALLY NEEDED.
Other Protective Equipment:
Work Hygienic Practices:CUSTOMARY GOOD HYGIENE.
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:>500F/257C
Vapor Density:>1
Spec Gravity:0.90
Evaporation Rate & Reference:Solubility in Water:NIL
Appearance and Odor:LIGHT YELLOW, OILY LIQUID; NOT OBJECTIONABLE ODOR.
Percent Volatiles by Volume:NIL

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:
Hazardous Decomposition Products:CO, CO*2, H*2S(TRACE)
Conditions to Avoid Polymerization:

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,



expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.