

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)
Product name	SYNPOWER® 75W-140 LIMITED SLIP SYNTHETIC GEAR OIL	
Product code	VV982	
Product Use Description	No data	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid,, amber

CAUTION! PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION.

Potential Health Effects

Exposure routes

Inhalation, Eye Contact, Ingestion, Skin contact

Eye contact

Unlikely to cause eye irritation or injury.

Skin contact

Unlikely to cause skin irritation or injury. Prolonged or repeated contact may dry and crack the skin.

Ingestion

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

Inhalation

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

It is possible to breathe this material under certain conditions of handling and use (for example, during heating, spraying, or stirring). Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

There are no data available for assessing risk to the fetus from maternal exposure to this material.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Concentration
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	>=30-<40%

4. FIRST AID MEASURES

Eyes

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: No information available.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water spray, Dry powder, Foam, Carbon dioxide (CO₂) Dry chemical, Foam, Carbon dioxide (CO₂)

Hazardous combustion products

May form: carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, various hydrocarbons

Precautions for fire-fighting

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). DO NOT direct a solid stream of water or foam into hot, burning pools of liquid since this may cause frothing and increase

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

fire intensity. Frothing can be violent and possibly endanger any firefighter standing too close to the burning liquid.

Flammability Class for Flammable Liquids
Combustible Liquid Class IIIB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Spills of this material are very slippery.

Environmental precautions

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

Methods for cleaning up

Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, floor absorbent, or other absorbent material and shoveled into containers.

Other information

Notify the proper authorities as required that a spill has occurred. Comply with all applicable federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed.

Storage

Store in a cool, dry, ventilated area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

Exposure Guidelines

**HYDROTREATED LIGHT
PARAFFINIC DISTILLATE**

64742-55-8

ACGIH	time weighted average	5 mg/m3	Mist.
ACGIH	Short term exposure limit	10 mg/m3	Mist.
ACGIH NIC	time weighted average	0.2 mg/m3	Inhalable fraction.

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Wear resistant gloves such as:

Nitrile rubber

Respiratory protection

Respiratory protection is not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

Physical state	liquid
Form	No data
Colour	amber
Odour	mild
Boiling point/boiling range	330.00 °C / 626 °F@ 1,013.33 hPa
pH	No data
Flash point	(>)390 °F / 199 °C, Cleveland open cup
Evaporation rate	< 1 (Ethyl Ether)
Explosion limits	1 %(V) 6 %(V)
Vapour pressure	1.33 hPa @ 68 °F / 20 °C
Vapour density	(>) 1 (AIR=1)
Density	0.874 g/cm ³ @ 60.01 °F / 15.56 °C 7.29 lb/gal
Solubility	No data
Partition coefficient: n-octanol/water	No data
log Pow	no data available
Autoignition temperature	No data

10. STABILITY AND REACTIVITY

Stability

Stable

Conditions to avoid

Avoid contact with:, excessive heat

Incompatible products

Avoid contact with:, strong oxidizing agents

Hazardous decomposition products

May form:, carbon dioxide and carbon monoxide, oxides of sulfur, nitrogen and phosphorus, zinc oxide, various hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	no data available
---	-------------------

Acute inhalation toxicity

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	no data available
---	-------------------

Acute dermal toxicity

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	no data available
---	-------------------

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Fish

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

Proposition 65 warnings are not required for this product based on the results of a risk assessment.

SARA Hazard Classification Acute Health Hazard

New Jersey RTK Label Information

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
POLYMER	NJTS 254504001-5814
DIOCTYL ADIPATE	103-23-1
DI-TERT-BUTYL POLYSULFIDE	68937-96-2
Mineral Oil	NJTS 800986-5072P

Pennsylvania RTK Label Information

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
POLYMER	NJTS 254504001-5814
DIOCTYL ADIPATE	103-23-1
DI-TERT-BUTYL POLYSULFIDE	68937-96-2
Mineral Oil	NJTS 800986-5072P

Reportable quantity - Components

HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	none
--	------------	------

	Health	Flammability	Reactivity	Other
HMIS	1	1	0	
NFPA	1	1	0	

16. OTHER INFORMATION

ASHLAND
SAFETY DATA SHEET

Page: 9
Revision Date: 11/12/2009
Print Date: 2/23/2010
MSDS Number: R0388288
Version: 1.9

SYNPOWER® 75W-140 LIMITED
SLIP SYNTHETIC GEAR OIL
VV982

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).