

Weiman Granite and Stone Sealer

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Weiman Granite and Stone Sealer

Product Number: 34C, 115C
Product Use: Sealant.

Manufacturer/Supplier: Weiman Products

755 Tristate Parkway Gurnee, IL 60031

 Phone Number:
 1-800-837-8140

 Emergency Phone:
 1-800-535-5053

 Date of Preparation:
 October 7, 2013

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION

COMBUSTIBLE LIQUID. HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Eye: May cause eye irritation.

Skin: May cause skin irritation.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Because of its irritating properties, product may aggravate preexisting skin, eye, and respiratory conditions.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS#	Wt. %
Isopropanol	67-63-0	1 - 5
Ethylene glycol monobutyl ether	111-76-2	1 - 5

Section 4: FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water. If easy to do,

remove contact lenses, if worn. If irritation persists, get medical attention.

Skin Contact: In case of contact, immediately flush skin with plenty of water. Call a physician if

irritation develops and persists.



Weiman Granite and Stone Sealer

Inhalation: If breathed in, move person into fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical

personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately

(show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Combustible by WHMIS criteria.

Means of Extinction:

Suitable Extinguishing Media: Treat for surrounding material.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker

gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Scoop up material and place in a disposal container. Provide ventilation.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Use only in well-ventilated areas. Launder contaminated clothing before reuse. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed. Do not store at temperatures above 49 °C / 120 °F.



Weiman Granite and Stone Sealer

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Ingredient ACGIH-TLV
Isopropanol 200 ppm
Ethylene glycol monobutyl ether 20 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and

safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid.

Colour: Straw.

Odour: Solvent.

Odour Threshold: Not available.

Physical State: Liquid. pH: 8.2

Viscosity:Not available.Freezing Point:Not available.Boiling Point:Not available.

Flash Point: 58.8 °C (138 °F) TCC

Evaporation Rate:

Lower Flammability Limit:

Upper Flammability Limit:

Vapor Pressure:

Not available.

Not available.

Not available.

Not available.

Specific Gravity: 1.01

Solubility in Water:

Coefficient of Water/Oil Distribution:

Auto-ignition Temperature:

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.



Weiman Granite and Stone Sealer

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions. Keep in a cool place.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: None known.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon. Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

Ingredient LD₅₀ (oral) LC₅₀ Isopropanol 4396 mg/kg, rat 72.6 mg/L 4hr, rat 450 ppm 4hr, rat; Ethylene glycol monobutyl ether

470 mg/kg, rat 2.21 mg/L 4hr, rat

May cause eye irritation. Symptoms may include discomfort or pain, excess Eye:

blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, edema, drying,

defatting and cracking of the skin.

Ingestion: Harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

EFFECTS OF CHRONIC EXPOSURE

Target Organs: Not available.

Chronic Effects: Not hazardous by WHMIS criteria. Carcinogenicity: Not hazardous by WHMIS criteria.

Ingredient Chemical Listed as Carcinogen or Potential Carcinogen *

G-A4, I-3 Isopropanol G-A3, I-3 Ethylene glycol monobutyl ether

Mutagenicity: Not hazardous by WHMIS criteria.

Reproductive Effects: Not hazardous by WHMIS criteria.

Developmental Effects:

Teratogenicity: Not hazardous by WHMIS criteria. Embryotoxicity: Not hazardous by WHMIS criteria. Respiratory Sensitization: Not hazardous by WHMIS criteria.

Skin Sensitization: Not hazardous by WHMIS criteria. Toxicologically Synergistic Materials: Not available.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

^{*} See Section 15 for more information.



Weiman Granite and Stone Sealer

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

TDG Classification (Ground)

Not regulated

TDG Classification (Air)

UN1993; Flammable liquid, n.o.s. (Isopropanol); Class 3; PG III

IATA Classification (Air)

UN1993; Flammable liquid, n.o.s. (Isopropanol); Class 3; PG III

IMDG Classification (Vessel)

UN1993; Flammable liquid, n.o.s. (Isopropanol); Class 3; PG III

Section 15: REGULATORY INFORMATION

Federal Regulations

Canada: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Global Inventories

Ingredient

Canada

DSL/NDSL

Isopropanol

Ethylene glycol monobutyl ether

DSL

DSL

HMIS - Hazardous Materials Identification System

Health - 1 Flammability - 2 Physical Hazard - 0 PPE - B

NFPA - National Fire Protection Association:

Health - 1 Fire - 2 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

WHMIS Classification(s):

Class B3 - Combustible Liquid Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:







Weiman Granite and Stone Sealer

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen. A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen. A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: October 7, 2016

Version #: 2.1

Prepared by: Nexreg Compliance Inc.

Phone: (519) 488-5126

www.nexreg.com